

Cables & Connectors



OKC Cable Connection

CE-approved, fully insulated cable connections with neoprene rubber. Bayonet-type connection which locks firmly to provide safe and effective contact. The cable is fixed into a socket with two Allen screws.

| | |
|--------------------------------------|---------------------|
| OKC male 10-25mm ² ESAB | 0160 360 880 |
| OKC male 35-50mm ² ESAB | 0160 360 881 |
| OKC male 70-95mm ² ESAB | 0160 360 882 |
| OKC male 120mm ² ESAB | 0160 360 883 |
| OKC female 10-25mm ² ESAB | 0160 361 880 |
| OKC female 35-50mm ² ESAB | 0160 361 881 |
| OKC female 70-95mm ² ESAB | 0160 361 882 |
| OKC female 120mm ² ESAB | 0160 361 883 |
| OKC male 10-25mm Murex (Red) | 0701 416 257 |
| OKC male 25-50mm Murex (Red) | 0701 416 258 |
| OKC male 50-95mm Murex (Red) | 0701 416 259 |
| OKC female 10-25mm Murex (Red) | 0701 416 254 |
| OKC female 25-50mm Murex (Red) | 0701 416 255 |
| OKC female 50-95mm Murex (Red) | 0701 416 256 |
| OKC Adapter 25-50mm | 0590 046 800 |



ZBK Cable Connection

Fully insulated with neoprene rubber. Sturdy and robust with low contact resistance. The cable is fixed into a socket with two Allen screws. The two halves of the connection in a ZBK connection are identical and can therefore be interchanged in any order.

| | |
|---------------------------|---------------------|
| ZBK 25-35mm ² | 0265 902 482 |
| ZBK 50-70mm ² | 0265 902 481 |
| ZBK 95-120mm ² | 0265 902 480 |



OKC Machine Contacts & Angle Connection

The contacts should be mounted on the front panel of the machine and come in three dimensions. The angle connection is supplied as OKC 50-95 male and female.

| | |
|---|---------------------|
| OKC machine contact for OKC 25 | 0160 362 880 |
| OKC machine contact for OKC 50/95 | 0160 362 881 |
| OKC machine contact for OKC 120 | 0160 362 882 |
| Type 1 Angle connection, 1 male, 2 female | 0365 557 001 |
| Type 2 Angle connection, 2 male, 1 female | 0365 558 001 |



CC17/18 Connectors

These heavy-duty connectors feature the cone and bush design of cable connection. They have high quality black rubber boots with positive lock and seal. They will accept up to 70mm² copper or aluminium cable.

| | |
|-------------|---------------------|
| CC17 Plug | 0700 606 402 |
| CC18 Socket | 0700 606 403 |

This document was created with Win2PDF available at <http://www.win2pdf.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.
This page will not be added after purchasing Win2PDF.